



RED ENERGY SDN BHD (99405-H)

No. 22, Jalan Anggerik Mokara 31/59,
Seksyen 31, Kawasan Perindustrian Kota Kemuning, 40460
Shah Alam, Selangor, Malaysia.

TEL : + 603 5122 8881, FAX : + 603 5122 9991

WEBSITE: www.redenergy.com.my

E-MAIL: admin@redenergy.com.my

RUBBER PRODUCTS



RUBBER FOR PULLEY LAGGING

At drive pulleys, it's highly recommended to use diamond-groove profile to increase traction, minimize slippage and improve self-cleaning. This rubber comes with **special adhesive layer** to reduce chances of lagging peel-off.



Plain surface

Small diamond-
groove surface

Large diamond-
groove surface

*A = with adhesive layer
B = without adhesive layer*

Dimension [Thickness x Width x Length]
10 x 2,000 x 10,000 mm

*A lagging for all applications,
with a well-balanced mix
of strength, hardness and
resistance to abrasion*

DIN 53516
*Colour black, Elastomer SBR, IR
Hardness 60±5 Shore A DIN 53505
Rebound resilience 35% DIN 53512*



RUBBER FOR SKIRT BOARD

Proven performance in slurry handling application such as pipelines, chutes and tank lining, hydrocyclones, sumps etc. Also use in wide range of sealing problem.



Outstanding resilience & elasticity

Excellent sealing characteristic

Excellent shock, vibration and noise absorption properties

Sizes

Standard sheet size: 9.25m X 1.25 m; 1.5m X 10m

Standard thickness range : 2.0mm to 30mm (approx. 1/16" to 1 1/4")

Moulded components available

DIN 53516, *Abrasion resistance 210mm³*

Rebound Resilience 70% DIN53516

Hardness 45~60 IRHD



COLD JOINT & PATCHING COMPOUND

APPLICATION: COLD JOINT

For conveyor belt cold-joining process, use TL-T-70 for stronger adhesion and faster drying time.



TOPGUM TL-T 70

Complete set 1000 g solution + 70 g hardener

APPLICATION: COLD PATCHING

For conveyor belt cold-patching process, use RE Cold Repair Strip with bonding layer



on both sides.

RE Patching Strip, 1.8mm (thickness) x 220mm x 10mtrs.